

ZETA OD racks are designed for outdoor applications to meet the Ingress Protection(IP) rating system, defined by the International Electro-technical Commission (IEC) 60529 standard, which classifies and certifies the degree of protection offers against intrusion from solid objects (like dust) and liquids (like water). Racks are manufactured of Zinc coated steel sheet/CRCA Sheet punched, formed welded with a proper mechanical design. The rack frame perforation along with internal accessories create a highly flexible cabinet.

Product Summary:



Key Features:

- ✔ 100% assured compatibility with all equipment conforming to DIN 41494
- ✔ ISO 9001-2015, ISO 14001-2015, ISO 45001-2018 Certified Company
- ✔ Designed for outdoor applications
- ✔ Ingress protection Level: IP55
- ✔ Vandalism-proof Design. No point of access for lever-type tools
- ✔ Rain Canopy with or without Air filter as per required IP Standard
- ✔ 19inch mounting angle/ DIN Rail for equipment mounting
- ✔ Ventilation with adequate cooling fan & Filter/Without Ventilation
- ✔ Depth adjustable mounting slots.
- ✔ Wall/Pole Mounting option
- ✔ The highest protection against corrosion
- ✔ More than 110 Degree door opening (Optional)

Technical data:

Basic Construction	Welded
Basic Material in Use	Zinc coated steel sheet/CRCA Sheet
TOP AND BOTTOM	Welded, with necessary ventilation and Cable entry cutouts on bottom panel
SIDES & BACK	Welded
FRONT DOOR	Side hinged front single door with proper locking system
EQUIPMENT MOUNTING	DIN Standard 10mm. Square slots
STANDARD MOUNTING OPTION	Wall or Pole mounting brackets
COLOUR	Powder coated grey, black and customize finish
COLOUR PROTECTION	PP (polypropylene) Powder Coating
STATIC LOAD	40 Kg

Product basic codes and Dimensions:

RT code:	Height (U)	Width(mm)	Depth(mm)
ZOD-5540-4	4	550	400
ZOD-5545-4	4	550	450
ZOD-5550-4	4	550	500
ZOD-5540-6	6	550	400
ZOD-5545-6	6	550	450
ZOD-5550-6	6	550	500
ZOD-6040-6	6	600	400
ZOD-6045-6	6	600	450
ZOD-6050-6	6	600	500
ZOD-6060-6	6	600	600
ZOD-5540-9	9	550	400
ZOD-5545-9	9	550	450
ZOD-5550-9	9	550	500
ZOD-6040-9	9	600	400
ZOD-6045-9	9	600	450
ZOD-6050-9	9	600	500
ZOD-6060-9	9	600	600
ZOD-5540-12	12	550	400
ZOD-5545-12	12	550	450
ZOD-5550-12	12	550	500
ZOD-6040-12	12	600	400
ZOD-6045-12	12	600	450
ZOD-6050-12	12	600	500
ZOD-6060-12	12	600	600
ZOD-6040-15	15	600	400
ZOD-6045-15	15	600	450
ZOD-6050-15	15	600	500
ZOD-6060-15	15	600	600

Accessories (Optional):

1. Power Distribution unit 5A Sockets with Fuse/ Power Distribution Unit 15A Sockets with 16A MCB
2. Pole mounting bracket
3. Cantilever tray
4. Cooling FAN 230V AC 90 CFM
5. Hardware nut packet
6. Horizontal Cable manager
7. DIN Rail

ZETA OD racks (IP66) are designed for outdoor applications to meet the Ingress Protection (IP) rating system, defined by the International Electro-technical Commission (IEC)60529 standard, which classifies and certifies the degree of protection offers against intrusion from solid objects (like dust) and liquids (like water). Racks are manufactured of Zinc coated steel sheet punched, formed welded with a proper mechanical design. The rack along with internal accessories create a highly flexible cabinet.

Product Summary:



Key Features:

- ✔ Ingress protection Level: IP66
- ✔ 100% assured compatibility with all equipment conforming to DIN 41494
- ✔ Designed for outdoor applications
- ✔ Vandalism-proof Design. No point of access for lever-type tools
- ✔ Rain Canopy as per required IP Standard
- ✔ 19inch mounting angle/ DIN Rail for equipment mounting
- ✔ Depth adjustable mounting slots.
- ✔ The highest protection against corrosion
- ✔ More than 110 Degree door opening (Optional) ✔ Welded form Wall/Pole mounting Option

Technical data:

Basic Construction	Welded
Basic Material in Use	Zinc coated steel sheet
TOP AND BOTTOM	Welded, with necessary ventilation and Cable entry cutouts on bottom panel
SIDES & BACK	Welded
FRONT DOOR	Side hinged front single door with proper locking system
EQUIPMENT MOUNTING	DIN Standard 10mm. Square slots
STANDARD MOUNTING OPTION	Wall or Pole mounting brackets
COLOUR	Powder coated grey, black and customize finish
COLOUR PROTECTION	PP (polypropylene) Powder Coating
STATIC LOAD	40 Kg

Product basic codes and Dimensions:

RT code:	Height (U)	Width(mm)	Depth(mm)
ZOD-66-5540-4	4	550	400
ZOD-66-5545-4	4	550	450
ZOD-66-5550-4	4	550	500
ZOD-66-5540-6	6	550	400
ZOD-66-5545-6	6	550	450
ZOD-66-5550-6	6	550	500
ZOD-66-6040-6	6	600	400
ZOD-66-6045-6	6	600	450
ZOD-66-6050-6	6	600	500
ZOD-66-6060-6	6	600	600
ZOD-66-5540-9	9	550	400
ZOD-66-5545-9	9	550	450
ZOD-66-5550-9	9	550	500
ZOD-66-6040-9	9	600	400
ZOD-66-6045-9	9	600	450
ZOD-66-6050-9	9	600	500
ZOD-66-6060-9	9	600	600
ZOD-66-6040-12	12	600	400
ZOD-66-6045-12	12	600	450
ZOD-66-6050-12	12	600	500
ZOD-66-6060-12	12	600	600
ZOD-66-6040-15	15	600	400
ZOD-66-6045-15	15	600	450
ZOD-66-6050-15	15	600	500
ZOD-66-6060-15	15	600	600

Accessories (Optional):

1. Cantilever tray
2. Hardware nut packet
3. Horizontal Cable manager
4. Pole mounting bracket
5. DIN Rail