



Key Features

1. Conforms to DIN 41494/EIA310/ Equivalent Standard
2. Design & Construction confirms to Industry Standard
3. 19 inch mounting angle for equipment mounting
4. 500 Hrs. Salt Spray Test Certified on Powder Coating for better durability
5. Top & Bottom Cover with Cable Entry provision and rubber grommet
6. Ventilation with adequate cooling fan.
7. Mounting channel movement with adjustable depth
8. Available in CKD or Welded form
9. ISO 9001, ISO 14001 & ISO 45001 Certified

Technical details

Basic construction	Welded or CKD
Basic material in use	High Grade C.R.C.A Sheet of various sheet thickness
Top Cover	Top Cover with Cable entry and 1 /2 Fan mounting provision
Bottom Cover	Bottom Cover with Cable entry provision
Front Door	Toughened glass with metal channel holding and lock
Standard Mounting	19 inch, DIN41494 Std. Front & Rear with adjustable depth
Color	Powder coated grey, black and customize finish
Side Panel	Detachable or Integrated
Color protection	Powder Coating
Load capacity	40 KGS

Ordering Information

PART Code	Height (U)	Width(mm)	Depth (mm)
ZWM-5540-4	4	550	400
ZWM-5550-4	4	550	500
ZWM-6040-6	6	600	400
ZWM-6050-6	6	600	500
ZWM-6060-6	6	600	600
ZWM-6050-9	9	600	500
ZWM-6060-9	9	600	600
ZWM-6050-12	12	600	500
ZWM-6060-12	12	600	600
ZWM-6050-15	15	600	500
ZWM-6050-15	15	600	600

Accessories (Optional)

1. Power Distribution unit 3-6 sockets 5A or 5/15A
2. Cantilever Tray
3. 19" Cable Manager 1U
4. Earthing Kit
5. 230V AC 90 CFM Fan
6. Mounting Hardware